

PARKER FREEZE DRY

A DIVISION OF PROFORM FABRICATION

PARKER 6



Parker 6

Heatcraft Magna
Refrigeration
Condenser Skid



DESCRIPTION

SPECIFICATION

CART CAPACITY _____	6
CHAMBER DIMENSION (DOOR OPEN) _____	300L x 84W x 100H Inches
REFRIGERATION SKID _____	Heatcraft Magna
REFRIGERATION DIMENSIONS _____	237L x 50W x 60H Inches
PAN DIMENSION _____	26L x 18W x 1H Inches
MAXIMUM HEATED PRODUCT PANS _____	252
USABLE SHELF AREA _____	819 Sq Ft
SHELF TEMP RANGE _____	-50 to 180 F
MAXIMUM VACUUM _____	≤ 0.01 mbar
MEDIAN WEIGHT CAPACITY _____	1500 lbs
ICE CONDENSER CAPACITY _____	2510 lbs
CHAMBER STANDARD OPERATING (dB) _____	85
CONDENSOR OPERATING (dB) _____	85
POWER REQUIREMENTS _____	480V 3 Phase
SUCTION TEMP _____	-60 F
TYPICAL MAX POWER USAGE _____	128 FLA
PLC OPERATING SYSTEM _____	Windows 10

PARKER FREEZE DRY

A DIVISION OF PROFORM FABRICATION

PARKER 6



42-H Carts

WHAT ARE THE BENEFITS TO FREEZE DRYING?

- Physical structure of the product remains unchanged
- Refrigeration and preservatives are unnecessary
- Product volume remains without changes to pliability
- Fast preparation for consumption with water
- Protection against spoilage

WHAT IS INVOLVED IN THE MAINTENANCE OF A PARKER 2?

- Clean debris from cooling coils every quarter
- Change oil in the pumps and boosters bi-annually
- Tighten all refrigerant connections monthly
- Tighten all fasteners bi-annually
- Follow all guidelines provided at the time of startup



Leybold Dry
Screw Pump
and Booster
Parker 2 Pictured



42H Cart